



# HYDRAULIC

## 2SNK UHMW HOSE

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BURST (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
XF2SNK-04UHMW	1/4	.535	<b>6,550</b>	28,275	1.77	0.28
XF2SNK-06UHMW	3/8	.693	<b>5,600</b>	23,925	2.76	0.43
XF2SNK-08UHMW	1/2	.819	<b>5,000</b>	20,300	3.54	0.55

- // 300 TIMES BETTER ABRASION RESISTANCE VS STANDARD HOSE
- // SUPERIOR OZONE AND LOW TEMPERATURE RESISTANCE

*Recommended for:* Applications which meet or exceed DIN 2SNK. Medium pressure hydraulic oil lines.

*Tube:* Black, oil resistant, Nitrile (NBR)

*Reinforcement:* Two wire high tensile steel braid.

*WearGuard Cover:* Black, oil and abrasion resistant Neoprene (CR), MSHA Approved with UHMW.

*Temperature:* -40° F to 250° F

*Recommended coupling:* 1J, 1W, 1Y, Two-Piece

ISO 9001:2015 CERTIFIED QUALITY SYSTEM  
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM