









# HYDRAULIC

## SUPER ABRASION RESISTANT R16 HOSE

PART NUMBER	JONES ID#	 HOSE I.D. (IN.)	 HOSE O.D. (IN.)	 RATED W.P. (PSI)	 MIN. BURST (PSI)	 MIN. BEND RADIUS (IN.)	 WT. PER FT. (LBS)
S150-04UHMW	<b>R16-04</b>	1/4	0.52	<b>5,800</b>	23,200	2.00	0.17
S150-06UHMW	<b>R16-06</b>	3/8	0.67	<b>4,800</b>	19,200	2.50	0.30
S150-08UHMW	<b>R16-08</b>	1/2	0.81	<b>4,000</b>	16,000	3.50	0.35
S150-10UHMW	<b>R16-10</b>	5/8	0.94	<b>3,500</b>	14,500	4.00	0.41
S150-12UHMW	<b>R16-12</b>	3/4	1.08	<b>3,000</b>	12,400	4.75	0.50
S150-16UHMW	<b>R16-16</b>	1	1.38	<b>2,400</b>	9,600	6.00	0.75

*Recommended for:* Applications which meet or exceed SAE 100R16. Medium pressure hydraulic oil lines

*Tube:* Black, oil resistant, Nitrile (NBR)

*Reinforcement:* Two wire braid of high tensile steel.

*WearGuard Cover:* Black, oil and abrasion resistant Neoprene (CR). MSHA approved.

*Temperature:* -40° F to 250° F

*Recommended coupling:* 1J, 1W, & two-piece

**300 TIMES BETTER ABRASION RESISTANCE VS STANDARD HOSE // SUPERIOR OZONE AND LOW TEMPERATURE RESISTANCE**

**ISO 9001:2015 CERTIFIED QUALITY SYSTEM  
API COMPLIANT QUALITY MANAGEMENT SYSTEM**

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM