



# HYDRAULIC

## SUPER ABRASION RESISTANT R17 HOSE

PART NUMBER	JONES ID#	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BURST (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
S151-04UHMW	<b>R17-04</b>	1/4	0.53	<b>3,000</b>	12,000	2.00	0.16
S151-06UHMW	<b>R17-06</b>	3/8	0.68	<b>3,000</b>	12,000	2.50	0.23
S151-08UHMW	<b>R17-08</b>	1/2	0.80	<b>3,000</b>	12,000	3.50	0.28
S151-10UHMW	<b>R17-10</b>	5/8	1.00	<b>3,000</b>	12,000	4.00	0.49
S151-12UHMW	<b>R17-12</b>	3/4	1.16	<b>3,000</b>	12,000	4.75	0.57
S151-16UHMW	<b>R17-16</b>	1	1.49	<b>3,000</b>	12,000	6.00	0.90

*Recommended for:* Applications which meet or exceed SAE 100R17. Medium pressure hydraulic oil lines.

*Tube:* Black, oil resistant, Nitrile (NBR)

*Reinforcement:* One wire high tensile steel braid in sizes 1/4" – 1/2". Two wire high tensile steel braid in sizes 5/8" – 1".

*WearGuard Cover:* Black, oil and abrasion resistant Neoprene (CR), MSHA Approved.

*Temperature:* -40° F to 250° F

*Recommended coupling:* 1J, 1W, 1Y, Two-Piece

**300 TIMES BETTER ABRASION RESISTANCE VS STANDARD HOSE // SUPERIOR OZONE AND LOW TEMPERATURE RESISTANCE**

**ISO 9001:2015 CERTIFIED QUALITY SYSTEM**  
**API COMPLIANT QUALITY MANAGEMENT SYSTEM**

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM