



# INDUSTRIAL



## RFD FUEL DISCHARGE 150 PSI HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT.
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	BAR	(LBS)
RFD-12	0.75	19	1.06	27	150	10	0.52
RFD-16	1	25	1.37	35	150	10	0.65
RFD-20	1.25	32	1.65	42	150	10	0.80
RFD-24	1.50	38	1.88	48	150	10	0.94
RFD-32	2	51	2.44	62	150	10	1.26
RFD-40	2.50	63	2.95	75	150	10	1.90
RFD-48	3	76	3.46	88	150	10	2.20
RFD-56	3.50	89	4.09	104	150	10	2.60
RFD-64	4	102	4.56	116	150	10	2.85
RFD-80	5	127	5.59	142	150	10	4.20
RFD-96	6	152	6.53	166	150	10	5.30

*Tube:* NBR

*Reinforcement:* Plies of Synthetic Cords with Anti-static Copper Wires

*Cover:* Synthetic Rubber Blended | Weather, Oil, Ozone, Abrasion Resistant

*Temperature:* -4° F to 185° F (-20° C to 85° C)

*Application(s):* Gas or petroleum oil delivery from tank truck | aromatic up to 50%

*Offered Length(s):* 100 & 200 foot

*Safety Factor:* 3 : 1

*Branding:* NRP JONES PETRO FD RFD (SIZE) FUEL DISCHARGE 150 PSI

ISO 9001:2015 CERTIFIED QUALITY SYSTEM  
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA