



INDUSTRIAL



THD PETRO 300 PSI TANK TRUCK HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN.)	VACUUM (BAR)
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	BAR			
THD-12	0.75	19	1.14	29	300	20	0.60	4.92	0.9
THD-16	1	25	1.37	35	300	20	0.86	5.90	0.9
THD-20	1.25	32	1.65	42	300	20	1.03	7.87	0.9
THD-24	1.50	38	1.92	49	300	20	1.20	10.03	0.9
THD-32	2	51	2.48	63	300	20	1.80	11.81	0.9
THD-40	2.50	63	3.03	77	300	20	2.40	13.97	0.9
THD-48	3	76	3.54	90	300	20	2.90	18.11	0.9
THD-56	3.50	89	4.09	104	300	20	3.60	20.86	0.9
THD-64	4	102	4.64	118	300	20	4.10	24.01	0.9
THD-80	5	127	5.62	143	300	20	6.80	27.55	0.9
THD-96	6	152	6.77	172	300	20	9.00	31.49	0.9

Tube: Oil & water resistant synthetic rubber

Reinforcement: Synthetic yarn fabric with steel wire helix

Cover: Synthetic rubber resistant to ozone, oil, weather and abrasion

Temperature: -20° F to 185° F (-29° C to 85° C)

Application(s): Commercial gasolines, diesel oils & other petroleum products including 51% aromatic content such as gasoline

Offered Length(s): 100 & 200 feet

Safety Factor: 3 : 1

Branding: NRP JONES PETRO HD THD (SIZE) PETRO HD 300 PSI FUEL S&D

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA