



INDUSTRIAL



TT PETRO 150 PSI TANK TRUCK HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN.)	VACUUM BAR
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	BAR			
TT-16	1	25	1.38	35	150	10	0.50	5.91	0.9
TT-24	1.5	38	1.89	48	150	10	1.10	10.03	0.9
TT-32	2	51	2.44	62	150	10	0.94	11.81	0.9
TT-48	3	76	3.54	90	150	10	2.70	18.11	0.9
TT-64	4	102	4.02	117	150	10	2.55	23.62	0.9
TT-96	6	152	6.61	168	150	10	4.97	33.46	0.9
TT-16100	1	25	1.38	35	150	10	0.50	5.91	0.9
TT-24100	1.5	38	1.89	48	150	10	1.10	10.03	0.9
TT-32100	2	51	2.44	62	150	10	0.94	11.81	0.9
TT-48100	3	76	3.54	90	150	10	2.70	18.11	0.9
TT-64100	4	102	4.02	117	150	10	2.55	23.62	0.9
TT-96100	6	152	6.61	168	150	10	4.97	33.46	0.9

Tube: NBR Blend

Reinforcement: Plies of Synthetic Cords with Steel Helix and Anti-static Copper Wire

Cover: SBR Blended, Weather, Oil, Ozone, Abrasion Resistant

Temperature: -20° F to 185° F (-29° C to 85° C)

Application(s): Commercial gasolines, diesel oils & other petroleum products (51% aromatic)

Offered Length(s): 100 & 200 feet

Safety Factor: 3 : 1

Branding: NRP JONES PETRO TT (SIZE) PETRO 150 PSI TANK TRUCK S&D

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA