



## WSC AQUA CORRUGATED 150 PSI HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN.)	VACUUM (BAR)
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	BAR			
WSC-12	0.75	19	1.14	29	150	10	0.69	5.11	0.9
WSC-16	1	25	1.37	35	150	10	0.80	6.29	0.9
WSC-20	1.25	32	1.65	42	150	10	0.96	8.26	0.9
WSC-24	1.50	38	1.88	48	150	10	0.75	9.84	0.9
WSC-32	2	51	2.44	62	150	10	1.01	11.81	0.9
WSC-40	2.50	63	2.95	75	150	10	1.96	15.74	0.9
WSC-48	3	76	3.46	88	150	10	1.61	18.90	0.9
WSC-56	3.50	89	4.01	102	150	10	2.90	17.71	0.9
WSC-64	4	102	4.56	116	150	10	2.22	23.62	0.9
WSC-80	5	127	5.55	141	150	10	5.20	39.37	0.9
WSC-96	6	152	6.53	166	150	10	4.50	47.24	0.9
WSC-128	8	203	8.77	223	150	10	11.20	59.05	0.9

*Tube:* Synthetic Rubber Blended

*Reinforcement:* Plies of Synthetic Cords with Helix Wire

*Cover:* Synthetic Rubber, Wrapped Type, Abrasion & Weather Resistant

*Temperature :* -4° F to 185° F (-20° C to 85° C)

*Application(s):* Handling of water, natural liquid fertilizer, inert fluid, sewage, waste water, mud where flexibility is required

*Offered Length(s):* 100 & 200 Foot

*Safety Factor:* 3 : 1

*Branding:* NRP JONES AQUA WSC (SIZE) AQUA 150 PSI S&D

**ISO 9001:2015 CERTIFIED QUALITY SYSTEM**  
**API COMPLIANT QUALITY MANAGEMENT SYSTEM**