



INDUSTRIAL



XLPE X-LINE CHEMICAL 260 PSI HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN)	VACUUM (BAR)
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	(BAR)			
XL-12	0.75	19	1.18	30	260	16	0.80	7.48	0.9
XL-16	1	25	1.37	35	260	16	1.39	8.26	0.9
XL-20	1.25	32	1.73	44	260	16	1.52	11.81	0.9
XL-24	1.50	38	1.96	50	260	16	2.00	13.77	0.9
XL-32	2	51	2.63	67	260	16	2.70	15.74	0.9
XL-40	2.50	63	3.11	79	260	16	3.20	19.68	0.9
XL-48	3	76	3.7	94	260	16	4.50	21.65	0.9
XL-64	4	102	4.72	120	260	16	4.80	27.55	0.9

Tube: Synthetic Rubber with XLPE Liner

Reinforcement: Plies of Synthetic Cords with Helix Wire

Cover: Green Color EPDM, Wrapped Type, Abrasion & Weather Resistant

Temperature: -4° F to 248° F (-20° C to 120° C)

Application(s): Petroleum based, hydrocarbon solvents, oxidising chemicals, strong acid/alkali, organics

Offered Length(s): 100 & 200 feet

Safety Factor: 3 : 1

Branding: NRP JONES X-LINK XL (SIZE) X-LINK CHEMICAL 250 PSI

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA