



INDUSTRIAL



1804 ROUGH NECK HOT OILER HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL) (IN.)	HOSE O.D. (NOMINAL) (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	BURST PRESSURE (MIN) (PSI)	BEND RADIUS (MIN) (IN.)	FITTING SIZE (IN.)	WT. PER FT. (LBS)
1804-24	1.50	2.15	2,250	3,375	6,750	20	1.50	1.78

Tube: Black | Nitrile Butadiene (NBR)

Reinforcement: Two plies of braided high-tensile strength steel wire

Cover: Black | Heat, oil, weather & abrasion resistant Neoprene (CR)

Temperature: -40° F to 300° F (-40° C to 148.8° C)

Application(s): Hot oil transfer at 275° F Continuous / 300° F Intermittent

Offered Length(s): 50 Feet

Safety Factor: 3:1

Branding: (Red Text on Clear Stripe) "NRP-JONES 1804 1 1/2 INCH ROUGH NECK HOT OILER HOSE 2250 PSI MAX W.P. TEMP. 275° f CONTINUOUS 300° f INTERMITTENT MADE IN USA (LOT NUMBER)"

Packaging: Coils

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API COMPLIANT QUALITY MANAGEMENT SYSTEM

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA



AS A MANUFACTURER OF HYDRAULIC HOSE AND FITTINGS,
INDUSTRIAL HOSE, AND OILFIELD HOSE,

NRP JONES IS DEDICATED TO EXCEEDING YOUR— AND YOUR CUSTOMERS'— EXPECTATIONS.

NRP Jones has what it takes to build your business. Over a half-century of experience helps you build customer satisfaction while increasing your sales and profits.

QUALITY

Pride and craftsmanship result in the quality products that you require.

Product reliability will live up to your expectations.

NRP Jones ISO 9001:2015 Registered.

SERVICE

Select from a wide range of hose and fitting products.

Orders are shipped from a large inventory.

You can count on prompt, knowledgeable, friendly help every time you call.

Your business is taken personally.

VALUE

NRP Jones offers competitive pricing.

Distributor programs are available to increase your sales and margins.

We'll Go to Great Lengths to Meet Your Needs

PO BOX 310, LAPORTE, IN 46352-0310

P: 800-348-8868 // SALES@NRPJONES.COM

WWW.NRPJONES.COM

MADE IN THE USA